

Rigidur Nature Line joint adhesive



Material

- Industrial adhesive which contains no solvents or hazardous substances for the bonding of Rigidur H wall boards.

Area of use

- For the quick and easy bonding of Rigidur H gypsum fibreboards in wall, ceiling and roof structures in drywall construction and in combination with Rigidur H boards in wooden frame and prefabricated house construction.

Substrate properties

- All Rigidur H board thicknesses are suitable for bonding.
- Ensure that the short edges of the boards are clean, smooth and free of dust. Cuts must be made cleanly to ensure a maximum joint width of 1 mm.

Processing

- Rigidur Nature Line joint adhesive should be applied according to the Rigidur guidelines for wall, ceiling, roof. The guideline can be downloaded at www.rigidur.com.

Safety information

- As for all Rigips adhesive products, the safety datasheet for this product can be supplied to professional processors on request or found at www.rigidur.com.

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.

Rigidur Nature Line joint adhesive

Technical data			
Designation	Rigidur Nature Line joint adhesive		
Container size	Cartridge	310	[ml]
Material	Viscosity	40000 - 50000	[mPa s]
	pH value	4.5 - 6.5	
Processing	Material consumption	15	[ml/joint m]
	Processing time	ca. 10	[minutes]
	Processing temperature	7 bis 25	[°C]
	Coverage	ca. 15	[m ² /cartridge]
Storage	Can be stored for at least 12 months unopened. Use up open cartridges promptly. Store protected from frost.		

The values given in this product data sheet solely describe the performance characteristics of the products. Rigips-Systems also have far-reaching structural-physical and static properties, which can be found in our system documentation (e.g. Planen und Bauen).

The information in this publication is based on our current technical knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve the users of our products from the responsibility of carrying out their own inspections and tests, as they only represent general guidelines. They neither do imply any legally binding assurance of certain properties or of suitability for a particular application. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and regulations are observed. We reserve the right to modifications in the interests of technical advancement without prior notice.