



DECLARATION OF PERFORMANCE

No.: Rigips_Gipsplatte_Alue_LE_0613

Product Type

EN 14190 : Plasterboard laminated with aluminium foil 30 µm

Identification of the construction product

**Rigips Gipsplatte rückseitig kaschiert mit Alu-Folie 30 µm als Dampfbremse
Batch identification consists of the production date printed on the pallet label**

Intended use

**Gypsum plasterboard product from reprocessing: plasterboard laminated
with aluminium foil 30 µm as water vapour barrier for interior applications**

Manufacturer

**Saint-Gobain Rigips GmbH
Schanzenstraße 84
D-40549 Düsseldorf**

Systems of assessment and verification of constancy of performance

System 4

The initial type testing according to EN 14190 was performed by the manufacturer. A factory production control system in compliance with EN ISO 9001 : 2008 adapted to EN 14190 is established to ensure that the construction products conform with the declared performance characteristics.



Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0 (C.3)	EN 14190
Shear strength per fastener	NPD	EN 14190
Water vapour resistance factor	NPD	EN 14190
Thermal conductivity	NPD	EN 14190
Dangerous substances	NPD	EN 14190
Airborne sound insulation	see system documentation of Saint-Gobain Rigips GmbH	EN 14190
Impact resistance		
Acoustic absorption		


The performance of the product for which this DoP has been issued is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Dr. Rüdiger Vogel, Managing Director
(name and function)

Düsseldorf, 24.04.2018
(place and date of issue)



(signature)

Saint-Gobain Rigips GmbH
Schanzenstr. 84 • D-40549 Düsseldorf