



DECLARATION OF PERFORMANCE

No.: RigiLine_LE_0613

Product Type

EN 14190 : Plasterboard recuttings

Identification of the construction product

RigiLine

Batch identification consists of the production date printed on the pallet label

Intended use

**Gypsum plasterboard product from reprocessing: Recuttings from Rigips plasterboards (type DF according to EN 520) for interior applications:
EN 14190**

Manufacturer

**Saint-Gobain Rigips GmbH
Schanzenstraße 84
D-40549 Düsseldorf**

Systems of assessment and verification of constancy of performance

System 4

The initial type testing according to EN 14190 was performed by the manufacturer. A factory production control system in compliance with EN ISO 9001 : 2008 adapted to EN 14190 is established to ensure that the construction products conform with the declared performance characteristics.

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A2-s1, d0 (C.2)	EN 14190
Shear strength per fastener	NPD	EN 14190
Water vapour resistance factor	10	EN 14190
Thermal conductivity	0,25 W/(m*K)	EN 14190
Dangerous substances	NPD	EN 14190
Airborne sound insulation	see system documentation of Saint-Gobain Rigips GmbH	EN 14190
Impact resistance		
Acoustic absorption		

The performance of the product for which this DoP has been issued is in conformity with the declared performance.
 This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Dr. Rüdiger Vogel, Managing Director
 (name and function)

Düsseldorf, 24.04.2018
 (place and date of issue)


 (signature)

Saint-Gobain Rigips GmbH
 Schanzenstr. 84 • D-40549 Düsseldorf